

DECLARATION OF PERFORMANCE Nº: 32303353 - 3350

1. Product: AQUA MICROCEMENT SYSTEM READY TO USE.

2. Manufacturer: CIMENTART MICROCEMENT SL with address in: C/ Dr. Pedro Herrero nº5 San Juan de Alicante - 03550 (Alicante- Spain). www.grupocimentart.es

3. Intended use: Ready-to-use, 100% waterproof decorative coating for preparation and finishing of walls, floors, ceilings, and bathrooms. For indoor and outdoor use on cement, gypsum, drywall, tiles, and plaster.

4. Evaluation system EVCP: 4

5. Standards tested and notified organizations: UNE-EN 13813:2014 & UNE-EN 15824:2017.

Essays No. 25/32303353, dated April 15, 2025 and Essays No. 25/32303350, dated April 22, 2025 in LGAI Technological Center S.A (Barcelona, Spain).

6. Declared performances:

Essential Features	Performances	Harmonized technical specifications
Fire reaction: RD 842/2013	Class A1	CE 424/2003
Initial tensile adherence: UNE-EN 13892-8	0,5 N/mm2	UNE-EN 13813:2014
Impact resistance: UNE-EN ISO 6272-1	14,7 n/mm2	
Abrasion resistance: BCA UNE-EN 13892-4	140 µm	
Liquid water permeability: UNE-EN 1062-3	0,04 Kg/m2 h05	UNE-EN 15824:2017
Direct traction adhesion: UNE-EN 1542	0,6 MPa	
Water vapor permeability: UNE-EN ISO 7783	0,003 g/h	
Hazardous substances	See Safety Data Sheet	

The performance of the product identified in point 1 is in accordance with the performance declared in point 6.

This declaration of performance is issued under the sole responsibility of the manufacturer indicated in point 2, in accordance with Regulation (EU) nº 305/2011.

Signed by and on behalf of the manufacturer:

Place and Date of Issue: in Alicante on 04/05/2025.

Technical Director: Juan Aranda Marín.





25

CIMENTART MICROCEMENT SL
C/ Dr, Pedro Herrero 5 CP: 03550 San Juan
Alicante (Spain)

AQUA MICROCEMENT SYSTEM

Nº: 32301975 - 1973

UNE-EN 13813:2014 & UNE-EN 15824:2017

Ready-to-use, 100% waterproof decorative coating for the preparation and finishing of walls, floors, ceilings, and bathrooms. For indoor and outdoor use on cement, gypsum, drywall, tiles, and plaster.

Fire reaction:

A1 Class

Adherence:

0,5 N/mm²

Impact resistance:

14,7 n/mm²

Abrasion resistance:

140 µm

Liquid water permeability:

0,04 Kg/m² h⁰⁵

Direct traction adhesion:

0,6 MPa

Water vapor permeability:

0,003 g/h

Hazardous substances:

See Safety Data Sheet